

P3345

Pelican™ 3345 VLO with Variable Light Output: The first pro-grade flashlight that automatically adjusts brightness.

It has a mind of its own. The Variable Light Output sensor (VLO) in the new Pelican™ 3345 VLO examines the ambient light/proximity and instantly adjusts its lumens to the most effective level. Now you can read pressure gauges close up or throw light hundreds of meters away - without hassling over manual power settings. The Variable Light Output sensor also makes the Pelican™ 3345 VLO one of our most energy efficient flashlights, preserving power and stretching battery life. Plus, the secondary flood beam illuminates potential trip hazards like loose cables, while the primary spot beam brightens long tunnels.

The integrated clip can be mounted to a safety vest for hands free lighting. With Class I, II, III, Division 1 /IECEx ia certifications and a full time battery level indicator, you can work in hazardous areas around the globe.



- Indicación de nivel de batería de tiempo completo
- Variable Light Output (automatically adjust to ambient light levels and proximity)
- Doble haz (concentrado y difuso)
- Safety Certified, Class I, II, III, Division 1/IECEx ia
- Integrated Clip
- 3 pilas alcalinas AA (no incluidas)


DIMENSIONES

longitud 7.25" (18.4 cm)

MATERIALES

cuerpo ABS
anillo de sellado de neopreno NBR
lente Polycarbonate (PC)
cubierta ABS
Clip ABS

COLORES

 High Visibility Yellow

LIGHT SPECS

tipo de sistema de iluminación LED
Lamp Secondary Type LED
duración de la lámpara 50000 hrs

POWER

tamaño de las pilas AA
tipo de pilas Alkaline
cantidad de pilas 3
Indicador del nivel de carga Full-time battery indicator
voltios 4.5v

PESO






peso con las pilas 7.5 oz (213 gr)
peso sin las pilas 5.0 oz (142 gr)

SWITCH

tipo de interruptor Push Button
modos de iluminación High

CERTIFICACIONES

- Class I, Division 1
- Class II, Division 1
- Class III, Division 1
- IECEX ia

FL1 STANDARD	SPOT / FLOOD	FLOOD	SPOT
	280 LUMENS	117 LUMENS	219 LUMENS
	5h 0mins	13h 15mins	9h 0mins
	126m	16m	137m
	3990cd	60cd	4724cd
	IPX7		

Document created on 11-30-18



DISTRIBUIDOR AUTORIZADO PARA ARGENTINA
 SUCRE 1852 - LOMAS DE ZAMORA
 (011) 4298-0184 delgasa@delga.com
www.delga.com